

°C	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100
100	60.25	56.19	52.11	48.00	43.87	39.71	35.53	31.32	27.08	22.80	18.49
0	100.00	96.09	92.16	88.22	84.27	80.31	76.33	72.33	68.33	64.30	60.25
°C	0	10	20	30	40	50	60	70	80	90	100
0	100.00	103.90	107.79	111.67	115.54	119.40	123.24	127.07	130.89	134.70	138.50
100	138.50	142.29	146.06	149.82	153.58	157.31	161.04	164.76	168.46	172.16	175.84
200	175.84	179.51	183.17	186.82	190.45	194.07	197.69	201.29	204.88	208.46	212.02
300	212.02	215.57	219.12	222.65	226.17	229.67	233.17	236.65	240.13	243.59	247.04
400	247.04	250.48	253.90	257.32	260.72	264.11	267.49	270.86	274.22	277.56	280.90
500	280.90	284.22	287.53	290.83	294.11	297.39	300.65	303.91	307.15	310.38	313.59
600	313.59	316.80	319.99	323.18	326.35	329.51	332.66	335.79	338.92	342.03	345.13
700	345.13	348.22	351.30	354.37	357.42	360.47	363.50	366.52	369.53	372.52	375.51
800	375.51	378.48	381.45	384.40	387.34	390.26	-	-	-	-	-

Tabla de Tolerancias -Precisión-

Temperatura °C	Valor Resistivo (Ohm)	tolerancias					
		°C	clase A	Ohm	°C	clase B	Ohm
-200	18.49	± 0.55		± 0.04	± 1.3°C		± 0.56
-100	60.25	± 0.35		± 0.14	± 0.8		± 0.32
0	100.00	± 0.15		± 0.06	± 0.3		± 0.12
100	138.00	± 0.35		± 0.13	± 0.8		± 0.30
200	175.84	± 0.55		± 0.20	± 1.3		± 0.48
300	212.02	± 0.75		± 0.27	± 1.8		± 0.64
400	247.04	± 0.95		± 0.33	± 2.3		± 0.79
500	280.90	± 0.15		± 0.38	± 2.8		± 0.93
600	313.59	± 0.35		± 0.43	± 3.3		± 1.06
650	329.51	± 0.45		± 0.46	± 3.6		± 1.13
700	345.13	-		-	± 3.8		± 1.17
800	375.51	-		-	± 4.3		± 1.28
850	390.23	-		-	± 4.6		± 1.34

Definición de clases de tolerancias

DIN clase A: $\pm(0.15+0.002 |t|)^{\circ}\text{C}$

DIN clase B: $\pm(0.30+0.005 |t|)^{\circ}\text{C}$

Cuando t es la temperatura actual del elemento de platino en °C